

# HPH J-HOOKS

### HIGH PERFORMANCE HYBRID









## **HPH CABLE CAPACITY**

#### 70 % FILL RATE CABLE CAPACITY CHART

Part No.	Area	Hook Diameter	CAT 5e Capacity	CAT 6 Capacity	Cat 6a Capacity
HPH16	1.07 in2	1"	20	15	10
HPH32	3.97 in2	2"	90	60	35
HPH48	9.26 in2	3"	200	150	80
HPH64	15.48 in2	4°	330	220	140

Cable capacity is calculated based on a 70% fill rate.

Actual capacity may vary due to CAT cable outside diameter variances by type and manufacturer.

Consult with the cable manufacturer to insure the correct cable outside diameter is being used during calculations.



## **HPH CABLE CAPACITY**

#### 100 % FILL RATE CABLE CAPACITY CHART

Part No.	Area	Hook Diameter	CAT 5e Capacity	CAT 6 Capacity	Cat 6a Capacity
HPH16	1.07 in2	1"	29	22	14
HPH32	3.97 in2	2"	129	86	50
HPH48	9.26 in2	3"	286	215	115
HPH64	15.48 in2	4"	472	315	200

Cable capacity is calculated based on a 100% fill rate.

Actual capacity may vary due to CAT cable outside diameter variances by type and manufacturer.

Consult with the cable manufacturer to insure the correct cable outside diameter is being used during calculations.